

IN THE CLAIMS:

1. (Previously Presented) A method for wireless communication among first and second integrated circuit devices within an enclosure, said method comprising the steps of:
  - 5 transmitting a signal using a first antenna associated with said first integrated circuit device in accordance with an ultra wide band wireless standard; and
  - receiving said signal using a second antenna associated with said second integrated circuit device within said enclosure.
- 10 2. (Original) The method of claim 1, wherein said first and second antennas are incorporated in said first and second integrated circuit devices.
- 3 (Original) The method of claim 2, wherein at least one of said first and second antennas is a pin on said first or second integrated circuit device.
- 15 4. ((Previously Presented) The method of claim 2, wherein at least one of said first and second antennas is fabricated on said first or second integrated circuit device
- 5 (Original) The method of claim 1, wherein said signal comprises one or more
- 20 channels.
- 6 (Original) The method of claim 1, wherein one or more signals are transmitted by said first antenna using one or more associated sub-carrier frequencies.
- 25 7. (Original) The method of claim 1, wherein said signal is time-division multiplexed.

8. (Original) The method of claim 1, wherein said signal is frequency-division multiplexed.

9. (Original) The method of claim 1, wherein said signal is spatially multiplexed.

10. (Original) The method of claim 1, wherein said enclosure is a housing of a self-contained device.

11. (Cancelled).

12. (Cancelled).

13. (Cancelled).

14. (Previously Presented) A method for wireless communication by an integrated circuit device within an enclosure, said method comprising the step of:

transmitting a signal using an antenna associated with said integrated circuit device in accordance with an ultra wide band wireless standard to a second integrated circuit device within said enclosure

15. (Original) The method of claim 14, wherein said signal comprises one or more channels.

16. (Original) The method of claim 14, wherein said enclosure is a housing of a self-contained device.

17. (Previously Presented) An integrated circuit device within an enclosure, comprising:

at least one circuit for transmitting a signal in accordance with an ultra wide band wireless standard; and

5 an antenna for transmitting said signal in accordance with said ultra wide band wireless standard to a second integrated circuit device within said enclosure.

18 (Original) The integrated circuit device of claim 17, wherein said signal comprises one or more channels.

10

19. (Original) The integrated circuit device of claim 17, wherein said enclosure is a housing of a self-contained device

20 (Original) The integrated circuit device of claim 17, wherein said antenna is  
15 incorporated in said integrated circuit device.

21. (Original) The integrated circuit device of claim 17, wherein said antenna is at least one pin of said integrated circuit device